



### HGS-A HYDRAULIC SWING BEAM SHEAR SPECIFICATIONS

MODEL	CUTTING LENGTH		CUTTING CAPACITY (45 kg/mm2)		CUTTING CAPACITY (70 kg/mm2)		CUTTING ANGLE	STROKE PER MINUTE	NUMBER OF HOLD DOWNS	PRESSURE	MAIN MOTOR	BACK GAUGE MOTOR	OIL CAPACITY	BLADE GAP ADJUSTMENT (min/max)	BACKGAUGE TRAVEL	BACKGAUGE SPEED	NUMBER OF SHEET SUPPORT ARMS	TABLE LENGTH		MACHINE WIDTH		TABLE HEIGHT		WIDHT	TANSPORT WIDTH	LENGTH	HEIGHT	WEIGHT
	A	Inch	Inch	Inch	Inch	1/min.												Amount	ton	HP	HP	Gallons	Inch					
HGS-A 2100-6	83	0.2	0.2	1.2	28	11	9	14.8	1.0	39.6	0.002-0.03	39	4.3	2	95.1	118.5	31	94.9	84.6	114.2	64.6	9900						
HGS-A 2600-6	102	0.2	0.2	1.2	20	13	10	14.8	1.0	39.6	0.002-0.03	39	4.3	2	114.2	118.5	31	94.9	84.6	133.9	64.6	11000						
HGS-A 3100-6	122	0.2	0.2	1.2	18	14	12	14.8	1.0	39.6	0.002-0.03	39	4.3	2	133.9	118.5	31	94.9	84.6	157.5	64.6	12100						
HGS-A 3600-6	142	0.2	0.2	1.2	15	16	14	14.8	1.0	39.6	0.002-0.03	39	4.3	3	154.7	118.5	31	94.9	84.6	174.8	65.0	13750						
HGS-A 4100-6	161	0.2	0.2	1.2	15	18	15	14.8	1.0	39.6	0.002-0.03	39	4.3	3	174.4	118.5	31	94.9	84.6	194.5	65.0	15400						
HGS-A 2100-8	83	0.3	0.2	1.5	20	11	12	20.1	1.0	52.8	0.002-0.04	39	4.3	2	96.5	119.7	31	96.5	85.6	137.2	65.0	10890						
HGS-A 2600-8	102	0.3	0.2	1.5	18	13	14	20.1	1.0	52.8	0.002-0.04	39	4.3	2	96.5	119.7	31	96.5	85.6	137.2	65.0	12650						
HGS-A 3100-8	122	0.3	0.2	1.5	16	14	18	20.1	1.0	52.8	0.002-0.04	39	4.3	2	135.8	119.7	31	96.5	85.6	158.5	65.0	14630						