

CMF CB Press Brake Specifications

	CB 44/2000	CB 44/2500	CB 70/2500	CB 70/3200	CB 88/2500	CB 88/3200	CB 110/2500
Pressing force (kN)	44	44	70	70	88	88	110
Working length	78"	98"	98"	126"	98"	126"	98"
Dist. between housings	62.5"	80.7"	79.5"	101"	79"	100"	76.9"
Depth of throat	7.9"	7.9"	9.8"	9.8"	9.8"	9.8"	12.6"
Stroke of the ram	4"	4"	4"	4"	4"	4"	5"
Approaching speed	236"	236"	213"	213"	213"	213"	189"
Working speed	19"	19"	19"	19"	19"	19"	23"
Returning speed	165"	165"	165"	165"	165"	165"	142"
Adjustment of ram travel	2.75"	2.75"	2.75"	2.75"	2.75"	2.75"	3.3"
Dist. between table and ram	13.3/8"	13.3/8"	13.2"	13.2"	13.78"	13.78"	15"
Motor power	5.25 HP	5.25 HP	7.25 HP	7.25 HP	7.25 HP	7.25 HP	10 HP
Weight	6600 lbs	7206 lbs	8800 lbs	9900 lbs	10100 lbs	12100 lbs	12320 lbs
Length	83"	103"	103"	130"	103"	130"	103"
Width	45"	45"	51"	51"	51"	51"	56"
Height	78"	82"	82"	86"	86"	87"	98"
	CB 110/3200	CB 110/4000	CB 138/2500	CB 138/3200	CB 138/4000	CB 176/3200	CB 176/4000
Pressing force (kN)	110	110	138	138	138	176	176
Working length	126"	157"	98"	126"	157"	126"	157"
Dist. between housings	100"	122"	76.7"	100"	122"	100.3"	122"
Depth of throat	12.6"	12.6"	12.6"	12.6"	12.6"	12.6"	12.6"
Stroke of the ram	5"	5"	5"	5"	5"	5.9"	5.9"
Approaching speed	189"	189"	189"	189"	189"	189"	189"
Working speed	23"	23"	19"	19"	19"	22"	22"
Returning speed	142"	142"	142"	142"	142"	142"	142"
Adjustment of ram travel	3.3"	3.3"	3.3"	3.3"	2.75"	4.3"	4.3"
Dist. between table and ram	15"	15"	15"	15"	15"	15.7"	15.7"
Motor power	10 HP	10 HP	10 HP	10 HP	10 HP	15 HP	15 HP
Weight	14520 lbs	18040 lbs	13860 lbs	16060 lbs	19140 lbs	19580 lbs	25300 lbs
Length	130"	162"	103"	130"	162"	130"	162"
Width	56"	56"	58"	58"	58"	61"	61"
Height	92"	97"	97"	97"	99"	97"	105"