

WC67Y Brake Specifications with E21

WC67Y model with E21	bending length (length of working table) inch	distance between frames (columns) inch	tonnage (power)	throat depth inch	beam stroke (stroke of ram) inch	day light (max opening between working table and ram) inch	beam approach speed (fast) - (speed or ram not working) IPM	beam working speed (slow) - (speed of ram working) IPM	beam return speed - (speed of ram back) IPM	oil capacity gallon	back gauge stroke inch	back gauge speed IPM	back ballscrew accuracy inch	motor power HP	length inch	width inch	height inch	height over floor inch	approx weight lbs.
WC67Y 30T/1300	51	43	33	9.8	3.1	12.2	142	16.5	118	30	20	472	0.001	4	78.7	63	74.8	29.5	5511
WC67Y 40T/2500	98.4	79.5	44	9.8	3.5	13.2	142	16.5	118	30	20	472	0.001	5.5	126	63	74.8	30.5	6393
WC67Y 63T/2500	98.4	79.5	70	9.8	4.3	13.7	142	16.5	118	30	20	472	0.001	7.5	126	67	84.6	31.9	8818
WC67Y 63T/3200	126	100	88	12.5	4.3	13.7	142	16.5	118	40	20	472	0.001	7.5	150	67	86.6	31.9	11023
WC67Y 80T/2500	98.4	79.5	88	12.5	4.7	14.5	165	16.5	118	30	24	472	0.001	7.5	126	71	87	32.6	12125
WC67Y 80T/3200	126	100	110	12.5	4.7	14.5	165	16.5	118	40	24	472	0.001	7.5	180	71	89	32.6	13228
WC67Y 100T/2500	98.4	79.5	110	12.5	4.7	15.3	165	16.5	118	40	24	472	0.001	10	126	71	89	32.8	14330
WC67Y 100T/3200	126	100	110	12.5	4.7	15.3	165	16.5	118	40	31	472	0.001	10	150	71	91	34.4	15432
WC67Y 100T/4000	157	124	110	12.5	4.7	15.3	165	16.5	118	45	31	472	0.001	10	181	71	93	34.8	16535
WC67Y 125T/2500	98.4	79.5	137	12.5	4.7	15.3	165	16.5	118	40	24	472	0.001	10	126	71	89	34.4	14991
WC67Y 125T/3200	126	100	137	12.5	4.7	15.3	165	16.5	118	50	24	472	0.001	10	150	71	91	34.4	16094
WC67Y 125T/4000	157	124	137	12.5	4.7	15.3	165	16.5	118	50	24	472	0.001	10	181	71	93	34.8	17196
WC67Y 160T/2500	98.4	79.5	176	12.5	7.9	18.7	177	16.5	118	45	24	472	0.001	15	126	74.8	94.4	870	17637
WC67Y 160T/3200	126	102	176	12.5	7.9	18.7	177	16.5	118	50	24	472	0.001	15	150	74.8	98	34.4	19842
WC67Y 160T/4000	157	124	176	12.5	7.9	18.7	177	16.5	118	60	24	472	0.001	15	193	74.8	101	34.8	24251
WC67Y 200T/2500	98.4	79.5	220	15.7	7.9	19.1	177	16.5	118	45	31	472	0.001	20	126	74.8	98.4	35.4	19842
WC67Y 200T/3200	126	102	220	15.7	7.9	19.1	177	16.5	118	50	31	472	0.001	20	154	74.8	101	37.4	23810
WC67Y 250T/3200	126	102	275	15.7	9.8	21	189	16.5	118	50	31	472	0.001	25	154	74.8	112	38.7	27558